

POWER PKG
KITS
SUPERCARGERS
CRATE ENGINES
CARBS & ACCESS.
FUEL PUMPS
GASKETS
INSTALL ITEMS
MANIFOLDS
EFI
HEADS
CAMS & ACCESS.
NITROUS
WATER PUMPS
ACCESS.
EXHAUST
SUSPENSION
SHOCKS
QWIKDATA2
INDEX



CYLINDER HEADS S/B CHRYSLER



SPECS: #61779

| | |
|-----------------------------|-------|
| Chamber volume..... | 58cc |
| Deck thickness | 5/8" |
| Valve spring diameter | 1.46" |
| Rocker stud diameter | 3/8" |
| Pushrod diameter (A) | 5/16" |
| Maximum valve lift..... | .580" |
| Bolt torque (G) | .95 |

| Intake | | Exhaust | |
|-------------------|-------|-------------------|-------|
| Port volume | 176cc | Port volume | 75cc |
| Valve size..... | 2.02" | Valve size..... | 1.60" |

FLOW DATA @ 28" H₂O

| Intake | | | | | | |
|---------|-------|-------|-------|-------|-------|-------|
| .100" | .200" | .300" | .400" | .500" | .600" | .700" |
| 62 | 119 | 175 | 225 | 251 | 260 | - |
| Exhaust | | | | | | |
| .100" | .200" | .300" | .400" | .500" | .600" | .700" |
| 52 | 105 | 142 | 169 | 185 | 190 | - |



CHRYSLER 318-360 V8



Performer RPM #61779

PERFORMER RPM CHRYSLER MAGNUM HEADS

- Designed for 1992 & later 5.2L (318 c.i.d.) and 1993 & later 5.9L (360 c.i.d.) Chrysler Magnum style V8s
- Match with the Edelbrock RPM Air-Gap Magnum manifold #7577 for maximum horsepower and torque (see page 75)
- Exhaust flanges in stock location to allow use of stock exhaust if desired
- Accepts widely available small-block Chevy adjustable rockers (1.6 ratio) and classic valve covers #4177 and #41773

Bare (single) Complete (single)

Performer RPM Chrysler Magnum.....#61769*#61779*

Important Notes: Requires hardened pushrods, #9638 (see page 171). Match with Edelbrock head gasket sets on pages 44-45. Recommended spark plugs 14mm x 3/4" reach with flat gasket seat (Champion RC12YC).

SPECS: #60779 | #60179

| | |
|------------------------------------|-----------|
| Chamber volume (60779/60179) | 63cc/65cc |
| Deck thickness | 5/8" |
| Valve spring diameter | 1.46" |
| Rocker stud diameter | — |
| Pushrod diameter (A) | 5/16" |
| Maximum valve lift..... | .575" |
| Bolt torque (G) | .95 |

| Intake | | Exhaust | |
|-------------------|-------|-------------------|-------|
| Port volume | 171cc | Port volume | 77cc |
| Valve size..... | 2.02" | Valve size..... | 1.60" |

FLOW DATA @ 28" H₂O

| Intake | | | | | | |
|---------|-------|-------|-------|-------|-------|-------|
| .100" | .200" | .300" | .400" | .500" | .600" | .700" |
| 69 | 129 | 188 | 232 | 249 | 251 | - |
| Exhaust | | | | | | |
| .100" | .200" | .300" | .400" | .500" | .600" | .700" |
| 64 | 108 | 142 | 171 | 183 | 190 | - |



Performer RPM Chrysler #60779

PERFORMER RPM CHRYSLER & CHRYSLER 340

- Performer RPM Chrysler heads deliver outstanding performance in non-emission 1967-91 Chrysler 318-340-360 c.i.d. engines
- Designed for non-emission 1968-73 340 c.i.d. Chryslers, RPM Chrysler 340 heads have chambers machined .060" for clearance with early high-compression engines
- These heads are capable of 417 horsepower and 397 ft/lbs. of torque on pump gas with an Edelbrock Performer RPM intake manifold and matching camshaft

Bare (single) Complete (single)

Performer RPM Chrysler.....#60769*#60779*
Performer RPM Chrysler 340.....#60199*#60179*

Important Notes: The special valvetrain in the 1970 340 T/A is not compatible with these heads. Match with Edelbrock head gasket sets on pages 44-45. Bare heads will have valve guides & seats installed, but will require final sizing & a valve job to match the valves you will be using. Recommended spark plugs 14mm x 3/4" reach with flat gasket seat (Champion RC12YC).

(A) Width of slot in guide plate
(B) Recommended valve sizes, not maximum

(C) Approximate figures
(D) Valves .120" longer than stock

(G) Head bolt torque in ft/lbs; studs use manufacturer's specs (see instructions for lube/sealer)